

CONSTRUCTION		COMPLIANCE	
Materials	Grade-A "One-Trip" Shipping Conex	OSHA	1910.106
Door	90 minute fire-rated steel door with panic bar and closer	NFPA	All booths are built meet NFPA 1, NFPA 30, NFPA 33, NFPA 58, NFPA 70, NFPA 91
Penetrations	Utility plate with pre-punched holes and seal offs to accomdate additional equipment.		
BOOTH SIZE		ELECTRICAL	
Dimensions	20' X 8' X 8'	(2) 115 volt rated 20A wall recepticles, (2) wall switches, (2) ceiling mounted LED lights, (2) Variable Frequency Drives, (1) UL-Listed 24x24 Control Panel, 3/4" rigid conduit *Additional wall switches and recepticles can be added at an additional price	
Square Footage	160 sq/ft		
Door Size	30-70 egress door		
AIR SYSTEM		HVAC	
Fans	(1) 850 CFM fan (1) 4600 CFM fan	100% Outside Sourced Air	
ACH	Base flow rate - 30 air changes per hour Purge flow rate - 215 air changes per hour		
ALARMS		TURN-KEY	
Gas Sensor	(1) Honeywell Sensepoint XCD gas monitor	This unit is "Plug-n-Play". Set it, anchor, power and water ready	
Audible Alarm	(1) audible alarm sounds @ 20% llower explosive limit		