

CONSTRUCTION		COMPLIANCE
<p>Materials 18 gauge metal panels</p> <p>Door 90 minute fire-rated steel door with panic bar and closer</p> <p>Penetrations Utility plate with pre-punched holes and seal offs to accomdate additional equipment.</p>	<p>California Fire Code 2019 International Fire Code 2018 NFPA 1 Fire Code 2018 Washington Fire Code 2018 (WAC 51-54A) California Mechanical Code 2019 International Mechanical Code 2018 Uniform Mechanical Code 2021</p>	
BOOTH SIZE		ELECTRICAL
<p>Dimensions 10' X 10' X 8'-6" (9'-8" with fans)</p> <p>Square Footage 100 sq/ft</p> <p>Door Size 30-70 egress door</p>	<p>(2) 115 volt rated 20A wall receptacles, (2) wall switches, (1) ceiling mounted LED lights, (2) Variable Frequency Drives, (1) UL-Listed 24x24 Control Panel, 3/4" rigid conduit</p> <p>*Additional wall switches and receptacles can be added at an additional price</p>	
AIR SYSTEM		HVAC
<p>Fans (2) 12" tube axial fans with spark-proof blades rated at 1400cfm</p> <p>ACH Base flow rate - 60 air changes per hour Purge flow rate - 112 air changes per hour</p>	<p>Not Available on this model.</p>	
ALARMS		TURN-KEY
<p>Gas Sensor (1) Honeywell Sensepoint XCD gas monitor</p> <p>Audible Alarm (1) audible alarm & (1) strobe activate @ 20% lower explosive limit</p>	<p>Turn-Key package includes on-site delivery and installation with finished conduit and electrical.</p> <p>OR you may decline the turk-key option for a price drop. Rigid 3/4" conduit roughed through the ceiling is provided. Remaining conduit and electrical must be finished by a qualified electrician.</p>	