

CONSTRUCTION		COMPLIANCE	
<b>Materials</b>	Grade-A "One-Trip" Shipping Conex	<b>OSHA</b>	1910.106
<b>Door</b>	90 minute fire-rated steel door with panic bar and closer	<b>NFPA</b>	All booths are built meet NFPA 1, NFPA 30, NFPA 33, NFPA 58, NFPA 70, NFPA 91
<b>Penetrations</b>	Utility plate with pre-punched holes and seal offs to accomdate additional equipment.		
BOOTH SIZE		ELECTRICAL	
<b>Dimensions</b>	40' X 8' X 8'	(4) 115 volt rated 20A wall recepticles, (2) wall switches, (4) ceiling mounted LED lights, (2) Variable Frequency Drives, (1) UL-Listed 24x24 Control Panel, 3/4" rigid conduit  *Additional wall switches and recepticles can be added at an additional price	
<b>Square Footage</b>	320 sq/ft		
<b>Door Size</b>	30-70 egress door		
AIR SYSTEM		HVAC	
<b>Fans</b>	(2) 18"tube axial fans with spark-proof blades rated at 5600cfm	Not Available on this model.	
<b>ACH</b>	Base flow rate - 45 air changes per hour  Purge flow rate - 105 air changes per hour		
ALARMS		TURN-KEY	
<b>Gas Sensor</b>	(1) Honeywell Sensepoint XCD gas monitor	This unit is "Plug-n-Play". Set it, anchor, power and water ready	
<b>Audible Alarm</b>	(1) audible alarm sounds @ 25% lower explosive limit		